

Maximise Creativity!



LAMPY creative lighting consoles by Showtec

The new Showtec Lampy DMX lighting controller: Maximise creativity

The new Showtec Lampy light controllers offer strong features and a very user-friendly and intuitive interface that makes shows easy, fast and fun to design and control.

The Showtec Lampy series consists of 2 models, the Lampy 20 with 10 multifunctional faders and the Lampy 40 with 30 multifunctional faders. Both are available in a 1 and 2 DMX universe version. The 2 universe versions offer next to the extra universe also ArtNet and sACN, groups, presets, fixture view, virtual playbacks, cue-list window and DMX output window on an external (touch) screen.

Via the optional Lampy DNGL, which is connected via a USB port, the 1 universe versions can be upgraded to 2 universes with the corresponding extra features.

Designing and controlling a light show for a small to medium sized set up has never been easier and never so enjoyable. Be surprised by the looks, the intuitive operation and the ease of use of the Showtec Lampy light controllers.



LAMPY

Light controllers Showtec



Showtec Light controllers

LAMPY





LAMPY 20 1U

50740 1 Universe 20-fader DMX console

Special features:

- DMX Console with state-of-the-art look and feel for controlling any static and moving light effect suited for various venues
- Clear workflow with large 10.1" touchscreen, multicolor indicator LEDs and four encoder wheels with 1.3" OLED display
- Intuitive virtual environment with Fixture View, Quick Color Picker, OSC and second screen possibility
- Easy control of advanced light effects with complete built-in effect engine for quickly accessing stunning effects
- Industrial floating design with cue list lighting and optional USB light
- Freely assignable 10 multifunction faders and 10 playback faders with 9 memory storage pages
- Optional Lampy dongle for more DMX channels, ArtNet, sACN and access to all external monitor features

Technical Information

Control Mode:	Manual / MIDI	Data Connector out:	RJ45 / USB
DMX Channels:	512	Midi Connector:	Yes
Display:	LCD / Touch	Ethernet Ports:	1
Display Size:	10.1"	Audio Triggers:	3
Display External:	Yes	Length (mm):	505 mm
Display External Resolution Width:	1920	Height (mm):	128 mm
Display External Resolution Height:	1080	Width (mm):	345 mm
Fixtures:	512	Weight:	8,8 kg
Buttons:	40	IP Rating:	IP20(indoor use only)
Cuelists:	90	Housing:	Metal / Plastic
Encoders Display:	4	Colour:	Black
Encoder Wheels:	4	Cooling:	Axial fan
Faders:	21	LED Indicators:	
OSC (Open Sound Control):	Yes	Operation mode / Output level / Output Level Mimic	
Playback Buttons:	20	Maximum Ambient Temperature:	40 °C
Playback Faders:	20	Minimum Ambient Temperature:	0 °C
Playback Pages:	9	Minimum Operating Temperature:	0 °C
sACN:	Optional	Reference Standard:	CE
Art-Net:	Optional	Included Cables:	ProPower Cable
Effects Engine:	Yes	Patch mode:	Yes
Universes:	1	Encoders Display Type:	OLED
Power Supply:	100-240VAC 50-60Hz 50 W	Desklight:	Built-in Worklight
Power Consumption:	50 W		
Power Connector in:	ProPower Blue		
DMX Connector out:	XLR 3P / XLR 5P		
Data Connector in:	USB		

The Showtec Lamy 20 1U is a fully featured DMX console with state-of-the-art look and feel designed to control static and moving light effects suited for various venues. Its industrial, floating design, with 10.1" touchscreen and multicolor indicator LEDs, enable a quick and clear workflow in an utmost intuitive manner.

Arranging existing elements is now easier than ever before with customizable workspaces and Fixture View for a clear virtual stage layout with easy pick, drag and drop control. You can also easily pick any color you'd like and control every moving light precisely to your desired outcome in no time. The Lamy 20 1U enables you to add an external (touch)screen and also to take full mobile control over your fixtures via an iPad or tablet, since it is OSC compatible.

You can easily create any complicated and stunning show effect with its complete built-in effect engine. Unlike most comparable DMX consoles, the Lamy 20 1U has no less than four encoder wheels with 1.3" OLED display for visual function information.

You can extend its software capabilities to two universes by adding an optional Showtec Lamy Dongle (50737). It doubles its DMX channels up to 1024, enables ArtNet, sACN and provide access to all external monitor features.

If 10 multifunction faders and 10 playback faders with cue buttons are not sufficient for your practice, we recommend to check out our Lamy 40 with 20 additional multifunction faders while using the same 9 memory pages for sufficient storage space.



LAMPY 20 2U

50741 2 Universe 20-fader DMX console

Special features:

- DMX Console with state-of-the-art look and feel for controlling any static and moving light effect suited for various venues
- Clear workflow with large 10.1" touchscreen, multicolor indicator LEDs and four encoder wheels with 1.3" OLED display
- Intuitive virtual environment with Fixture View, Quick Color Picker, OSC and second screen possibility
- Easy control of advanced light effects with complete built-in effect engine for quickly accessing stunning effects
- Industrial floating design with cue list lighting and optional USB light
- Freely assignable 10 multifunction faders and 10 playback faders with 9 memory storage pages
- Two DMX Universes with 1024 DMX channels, ArtNet, sACN and access to all external monitor features

Technical Information

Control Mode:	Manual / MIDI	DMX Connector out:	XLR 3P / XLR 5P
DMX Channels:	1024	Data Connector in:	RJ45 / USB
Display:	LCD / Touch	Data Connector out:	RJ45 / USB
Display Size:	10.1"	Midi Connector:	Yes
Display External:	Yes	Ethernet Ports:	1
Display External Resolution Width:	1920	Audio Triggers:	3
Display External Resolution Height:	1080	Length (mm):	505 mm
Fixtures:	1024	Height (mm):	128 mm
Buttons:	40	Width (mm):	345 mm
Cuelists:	90	Weight:	8,8 kg
Encoders Display:	4	IP Rating:	IP20(indoor use only)
Encoder Wheels:	4	Housing:	Metal / Plastic
Faders:	21	Colour:	Black
OSC (Open Sound Control):	Yes	Cooling:	Convection
Playback Buttons:	20	LED Indicators:	Operation mode /
Playback Faders:	20	Output level / Output Level Mimic	
Playback Pages:	9	Maximum Ambient Temperature:	40 °C
sACN:	Yes	Minimum Operating Temperature:	0 °C
Art-Net:	Yes	Reference Standard:	CE
Effects Engine:	Yes	Included Cables:	ProPower Cable
Universes:	2	Patch mode:	Yes
Power Supply:	100-240VAC 50-60Hz	Encoders Display Type:	OLED
Power Consumption:	50 W	Desklight:	Built-in Worklight
Power Connector in:	ProPower Blue		

The Showtec Lampy 20 2U is a fully featured DMX console with state-of-the-art look and feel designed to control static and moving light effects suited for various venues. Its industrial, floating design with 10.1" touchscreen and multicolor indicator LEDs enable a quick and clear workflow in an utmost intuitive manner.

Arranging existing elements is now easier than ever before with customizable workspaces and Fixture View for a clear virtual stage layout with easy pick, drag and drop control. You can also easily pick any color you'd like and control every moving light precisely to your desired outcome in no time.

The Lampy 20 2U enables you to add an external full HD (touch)screen and also to take full mobile control over your fixtures via an iPad or tablet since it is OSC compatible. You can easily create any complicated and stunning show effect with its complete built-in effect engine. Unlike most comparable DMX consoles, the Lampy 20 2U has no less than four encoder wheels with 1.3" OLED display for visual function information.

The Showtec Lampy 20 2U enables you to simultaneously control two standalone universes including all external monitor features and a second Fixture View. Its 1024 DMX channels are controllable via DMX, ArtNet and sACN.

If 10 multifunction faders and 10 playback faders with cue buttons are not sufficient for your practice, we recommend to check out our Lampy 40 2U with 20 additional multifunction faders while using the same 9 memory pages for sufficient storage space.

LAMPY

Light controllers Showtec



LAMPY 40 1U

50742 1 Universe 40-fader DMX console

Special features:

- DMX Console with state-of-the-art look and feel for controlling any static and moving light effect suited for various venues
- Clear workflow with large 10.1" touchscreen, multicolor indicator LEDs and four encoder wheels with 1.3" OLED display
- Intuitive virtual environment with Fixture View, Quick Color Picker, OSC and second screen possibility
- Easy control of advanced light effects with complete built-in effect engine for quickly accessing stunning effects
- Industrial floating design with cue list lighting and optional USB light
- Freely assignable 30 multifunction faders and 10 playback faders with 9 memory storage pages
- Optional Lampy dongle for more DMX channels, ArtNet, sACN and access to all external monitor features



Technical Information

Control Mode:	Manual / MIDI
DMX Channels:	512
Display:	LCD / Touch
Display Size:	10.1"
Display External:	Yes
Display External Resolution Width:	1920
Display External Resolution Height:	1080
Fixtures:	1024
Buttons:	60
Cuelists:	90
Encoders Display:	4
Encoder Wheels:	4
Faders:	41
OSC (Open Sound Control):	Yes
Playback Buttons:	40
Playback Faders:	40
Playback Pages:	9
sACN:	Optional
Art-Net:	Optional
Effects Engine:	Yes
Universes:	1
Power Supply:	100-240VAC 50-60Hz
Power Consumption:	60 W
Power Connector in:	ProPower Blue

DMX Connector out:	XLR 3P / XLR 5P
Data Connector in:	RJ45 / USB
Data Connector out:	RJ45 / USB
Midi Connector:	Yes
Ethernet Ports:	1
Audio Triggers:	3
Length (mm):	721 mm
Height (mm):	128 mm
Width (mm):	345 mm
Weight:	11,8 kg
IP Rating:	IP20(indoor use only)
Housing:	Metal / Plastic
Colour:	Black
Cooling:	Axial fan
LED Indicators:	Operation mode / Output level / Output Level Mimic
Maximum Ambient Temperature:	40 °C
Minimum Ambient Temperature:	0 °C
Minimum Operating Temperature:	0 °C
Reference Standard:	CE
Included Cables:	ProPower Cable
Patch mode:	Yes
Encoders Display Type:	OLED
Desklight:	Built-in Worklight

LAMPY DNGL

50737 USB Unlock Key

Special features:

- Unlock key for additional Lampy 20 and Lampy 40 features
- Second DMX universe with 512 additional DMX channels
- Full access to external monitor features (groups and presets, virtual playbacks, cuelist and DMX output)
- Second Fixture View
- Access to ArtNet and sACN protocols



Showtec Light controllers

LAMPY





LAMPY 40 2U

50743 2 Universe 40-fader DMX console

Special features:

- DMX Console with state-of-the-art look and feel for controlling any static and moving light effect suited for various venues
- Clear workflow with large 10.1" touchscreen, multicolor indicator LEDs and four encoder wheels with 1.3" OLED display
- Intuitive virtual environment with Fixture View, Quick Color Picker, OSC and second screen possibility
- Easy control of advanced light effects with complete built-in effect engine for quickly accessing stunning effects
- Industrial floating design with cue list lighting and optional USB light
- Freely assignable 30 multifunction faders and 10 playback faders with 9 memory storage pages
- Two DMX Universes with 1024 DMX channels, ArtNet, sACN and access to all external monitor features



Technical Information

Control Mode:	Manual / MIDI
DMX Channels:	1024
Display:	LCD / Touch
Display Size:	10.1"
Display External:	Yes
Display External Resolution Width:	1920
Display External Resolution Height:	1080
Fixtures:	1024
Buttons:	60
Cuelists:	90
Encoders Display:	4
Encoder Wheels:	4
Faders:	41
OSC (Open Sound Control):	Yes
Playback Buttons:	40
Playback Faders:	40
Playback Pages:	9
sACN:	Yes
Art-Net:	Yes
Effects Engine:	Yes
Universes:	2
Power Supply:	100-240VAC 50-60Hz
Power Consumption:	60 W
Power Connector in:	ProPower Blue

DMX Connector out:	XLR 3P / XLR 5P
Data Connector in:	RJ45 / USB
Data Connector out:	RJ45 / USB
Midi Connector:	Yes
Ethernet Ports:	1
Audio Triggers:	3
Length (mm):	721 mm
Height (mm):	128 mm
Width (mm):	345 mm
Weight:	11,8 kg
IP Rating:	IP20(indoor use only)
Housing:	Metal / Plastic
Colour:	Black
Cooling:	Axial fan
LED Indicators:	Operation mode / Output level / Output Level Mimic
Maximum Ambient Temperature:	40 °C
Minimum Operating Temperature:	0 °C
Reference Standard:	CE
Included Cables:	ProPower Cable
Patch mode:	Yes
Encoders Display Type:	OLED
Desklight:	Built-in Worklight

LAMPY DNGL

50737 USB Unlock Key

Special features:

- Unlock key for additional Lampy 20 and Lampy 40 features
- Second DMX universe with 512 additional DMX channels
- Full access to external monitor features (groups and presets, virtual playbacks, cuelist and DMX output)
- Second Fixture View
- Access to ArtNet and sACN protocols





Showtec **LAMPY** products are exclusively distributed by
Highlite International B.V. Vestastraat 2, 6468 EX Kerkrade, The Netherlands
sales@highlite.com Phone: +31-(0)45 - 5667701

