



## Showtec Spectral M3000 Zoom Q4 MKII

14 x 12W RGBW Osram LED Spot  
 Wide motorised zoom range (Pin Spot to Wash)  
 IP65 dust and water resistant  
 Smooth dimming & Strobe functions  
 DMX Master / Slave Control

### SOURCE

Light Source Type	LED
Light Source Quantity	14
Light Source Power	12W
Led Colour Type	RGBW
Refresh Rate (min)	900 Hz
Lumen Total	3900 lm

### OPTICAL

Beam Angle Circular (min)	8 deg
Beam Angle Circular (max)	40 deg
Zoom Type	Motorised

### CONTROL & PROGRAMMING

Control Mode	DMX, Stand Alone
DMX Channels	3,4,5,6,7,12,17
Protocols	DMX
Display	4 Segment LED

### DYNAMIC EFFECTS

Dimmer	0-100%
Strobe	0-20Hz

### MECHANICAL SPECS

#### RIGGING

Mounting Options	Clamp, Surface	Length	250mm
Safety Attachment	Yes	Width	275mm
		Height	375mm
		Weight	8.4kgs
		IP Rating	IP65

#### ELECTRIC SPECIFICATIONS & CONNECTIONS

Power Supply	100-240 VAC 50-60Hz	Housing	Aluminium Die Cast
Power Consumption	200W	Colour	Black

#### TERMAL SPECIFICATIONS

Power Connector in	PowerCON True 1 in (m)	Max Ambient Temp	40deg C
Power Connector out	PowerCON True 1 out (f)	Min Operating Temp	-10 deg C
DMX Connector	IP 65 XRL 3P & 5P IN/OUT		

### PRODUCT PROPERTIES

Cooling	Convection
---------	------------

### INCLUDED ITEMS

Included Cables	PowerCON True1
Included Accessories	User Manual
Included Rigging	Bracket, Safety Cable

### CERTIFICATIONS

Reference Standards	CE
---------------------	----



**Clearlight Shows Pty Ltd**