





Infinity iW 741 RDM


7 RGBW 40w OSRAM LEDs
Ultrafast movement & zoom range from 3.6 to 60 Deg
Selectable PWM Rate by DMX
Battery Powered Display
White output mode

<u>SOURCE</u>		<u>OPTICAL</u>	
Light Source Type LED		Beam Angle Circular (min)	3.6 deg
Light Source Quantity 7		Beam Angle Circular (max)	60 deg
Light Source Power 40W		Zoom Type	Motorised
Led Colour Type	RGBW		
Refresh Rate 6000 Hz		CONTROL & PROGRAMMING	
Lumen Total	3208 lm	Control Mode	DMX, Stand Alone
		DMX Channels	15, 20
<u>N</u>	<u> Movement</u>	Protocols	DMX, RDM
Pan	540	Display	LCD
Tilt	270	Dimming & Zoom Resolution	16bit
Pan/Tilt Resolution	16bit	MECHANICAL SPECS	
		Length	290mm
<u>RIGGING</u>		Width	204mm
Mounting Options	Quick Lock, Clamp	Height	418mm
Safety Attachment	Yes	Weight	9.3kgs
		IP Rating	IP20
ELECTRIC SPECIFIC	CATIONS & CONNECTIONS	Housing	Metal, Plastic
Power Supply	100-240 VAC 50-60Hz	Colour	Black
Power Consumption	295W		
Power Connector in	PowerCON Blue in (m)	TERMAL SPECIFICATIONS	
Power Connector out	PowerCON Grey out (f)	Max Ambient Temp	45deg C
DMX Connector	XRL 5P IN/OUT	Max Surface Temp	80 deg C

PRODUCT PROPERTIES INCLUDED ITEMS

Cooling		Axial Fan	Included Cables	PowerCON Cable
			Included Accessories	User Manual
	CERTIFICATIONS		Included Rigging	Quick Lock Bracket

Reference Standards



Clearlight Shows Pty Ltd