



Showtec Performer Profile Zoom150w Q6

150W RGBALC LED Zoom Spot
 Manual zoom of 25°-50° High CRI of 95
 Suitable for theatrical application
 DMX , RDM
 CCT colour temperature range of 1800K – 8000K

<u>SOURCE</u>		<u>OPTICAL</u>	
Light Source Type	LED	Zoom Minimum	25°
Light Source Quantity	1	Zoom Maximum	50 °
Light Source Power	150W	Zoom Ratio	1:2
Led Colour Type	RGBALC	Zoom Type	Manual
Refresh Rate (min)	1200 Hz		
Refresh Rate (max)	25 kHz		
Lux @ 2m	1588 lx		
Lumen Total	2624 lm		
<u>CONTROL & PROGRAMMING</u>			
CRI	95	Control Mode	DMX, Manual
CCT Minimum	1800K	DMX Channels	3,7,8,10,13,20
CCT Maximum	10000K	Protocols	DMX, RDM
		Display	1.3" OLED
<u>DYNAMIC EFFECTS</u>			
Dimmer	0-100%	<u>MECHANICAL SPECS</u>	
Strobe	0-25Hz	Length	568mm
		Width	224mm
		Height	191mm
<u>ELECTRIC SPECIFICATIONS & CONNECTIONS</u>			
Power Supply	100-240 VAC 50-60Hz	Weight	5.5kgs
Power Consumption	170W	IP Rating	IP20 (indoor only)
Power Connector in	PowerCON True 1 in (m)	Housing	ABS,Aluminum,Steel
Power Connector out	PowerCON True 1 out (f)	Colour	Black
DMX Connector	XRL 5P IN/OUT		
<u>TERMAL SPECIFICATIONS</u>			
<u>PRODUCT PROPERTIES</u>		Max Ambient Temp	45deg C
Cooling	Convection & Axial Fan		
<u>CERTIFICATIONS</u>		<u>INCLUDED ITEMS</u>	
Reference Standards	CE	Included Cables	PowerCON True1



Clearlight Shows Pty Ltd